

1/2 inch RF Coaxial Cable - LSZH Jacket



Product Code		
CC-12F		
Construction Material		
Inner Conductor	Material	Copper-clad aluminum
	Diameter mm	4.80 ± 0.05
Insulation	Material	Foam PE
	Diameter mm	12.30 ± 0.15
Outer Conductor	Material	Corrugated copper
	Diameter mm	13.80 ± 0.15
Jacket	Material	LSZH
	Color	Black
	Diameter mm	15.70 ± 0.20
Mechanical Specification		
Bend Radius mm	Single bend	70
	Repeated bend	125
Tensile Strength N		1050
Cable Weight kg/km		210
Recommended Temperature °C	Storage	-70~+85/-30~+80(LSZH)
	Installation	-40~+60/-25~+60(LSZH)
	Operating	-55~+85/-30~+80(LSZH)

Electrical Specification		
Impedance	50 ohm \pm 1.5 ohm	
Capacitance	76 pF/m	
Velocity	88%	
Insulation Resistance	10000 M Ω /km	
Peak Power	40 kW	
Peak Voltage	1800 V	
Cut-off Frequency	10 GHz	
Attenuation and Average power		
Maximum attenuation value shall be 105% of the nominal attenuation value		
Frequency MHz	Attenuation @20°C dB/100m	Average Power kW
200	3.10	2.44
450	4.75	1.59
800	6.46	1.17
1000	7.28	1.04
1500	9.09	0.84
1800	10.10	0.75
2000	10.70	0.71
2200	11.25	0.68
2500	12.10	0.62
3000	13.40	0.56
V.S.W.R.		
Frequency Band	VSWR	
800MHz~1000MHz	\leq 1.13	
1700MHz~2200MHz	\leq 1.13	
2200MHz~2700MHz	\leq 1.15	